



MATERIAL SAFETY DATA SHEET

Product Designation: Seaboard Grip-X

Section 1

Manufacturer's Name	Compression Polymers Corp.		
Address	801 Corey Street	Phone	570-346-8797
City, State, Zip	Moosic, PA 18507	FAX	570-346-5080
Date Prepared	December 22, 2004		

Section 2 - Hazardous Ingredients/Identity

This product has not been evaluated as a whole. However, some fumes may be released upon heating and the user must take the necessary precautions (ventilation, personal protective equipment, etc.) to protect employees from exposure (see Section 7 - Special Precautions)

Hazardous Component(s) chemical/common names	OSHA PEL	ACGIH PEL	Other Exp. Limits	%	CAS Number
Polyethylene Plastics	N/L	N/L	N/L	100	9002-88-4

This material is NOT HAZARDOUS by OSHA Communication definition.

Section 3 - Physical and Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	~.95	Vapor Pressure (mm Hg)	NA
Percent Volatility Volume (%)	NA	Vapor Density (Air = 1)	Solid	Evaporation Rate	NA
Solubility in Water	Insoluble		Reactivity in Water	None Known	
Appearance and Odor	White/translucent plastic pellets; faint aromatic odor				
Melting Point	220-280°F (104-138°C)				

This Material Safety Data Sheet and the information it contains are offered to you in good faith as accurate. We believe the information it contains to be correct but cannot guarantee its accuracy or completeness. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.



MATERIAL SAFETY DATA SHEET

Product Designation: Seaboard Grip-X

Section 1

Manufacturer's Name	Compression Polymers Corp.		
Address	801 Corey Street	Phone	570-346-8797
City, State, Zip	Moosic, PA 18507	FAX	570-346-5080
Date Prepared	December 22, 2004		

Section 2 - Hazardous Ingredients/Identity

This product has not been evaluated as a whole. However, some fumes may be released upon heating and the user must take the necessary precautions (ventilation, personal protective equipment, etc.) to protect employees from exposure (see Section 7 - Special Precautions)

Hazardous Component(s) chemical/common names	OSHA PEL	ACGIH PEL	Other Exp. Limits	%	CAS Number
Polyethylene Plastics	N/L	N/L	N/L	100	9002-88-4

This material is NOT HAZARDOUS by OSHA Communication definition.

Section 3 - Physical and Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	~.95	Vapor Pressure (mm Hg)	NA
Percent Volatility Volume (%)	NA	Vapor Density (Air = 1)	Solid	Evaporation Rate	NA
Solubility in Water	Insoluble		Reactivity in Water	None Known	
Appearance and Odor	White/translucent plastic pellets; faint aromatic odor				
Melting Point	220-280°F (104-138°C)				

This Material Safety Data Sheet and the information it contains are offered to you in good faith as accurate. We believe the information it contains to be correct but cannot guarantee its accuracy or completeness. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.