



### Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid If heated to more than 300°C, the product may form vapors of fumes which might cause respiratory irritation.
	Stable	X	
Incompatibility ( <i>Materials to Avoid</i> ) Attacked by oxidizing agents such as nitric or perchloric acid and free halogens. Also softened by hydrocarbons such as benzene, gasoline, lubricating oils, petroleum ether and by chlorinated hydrocarbons.			
Hazardous Decomposition or Byproducts Burning yields CO and CO <sup>2</sup>			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

### Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards ( <i>Acute and Chronic</i> ) No acute or chronic hazard.			
Carcinogenicity:	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure N/A			
Emergency and First Aid Procedures No acute hazard.			

### Section VII – Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled Sweep up and collect as essentially harmless organic wastes.	
Waste Disposal Method Dispose of in accordance with local, state and federal regulations. Recycle to process.	
Precautions to be Taken in Handling and Storing No specific requirements.	
Other Precautions Self-contained breathing apparatus for fire fighting personnel is recommended.	

### Section VIII – Control Measures

Respiratory Protection ( <i>Specific Type</i> ) Not generally required.				
Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical ( <i>General</i> )	N/A	Other	Normal working environment.
Protective Gloves Not generally required.		Eye Protection Safety glasses recommended.		
Other Protective Clothing or Equipment Not generally required.				
Work/Hygienic Practices Handle in accordance with good industrial hygiene and safety practices.				

USGPO 2010-491-529/45775